WISELEAF SCIENTIFIC VENTURES

SMART HEALTHCARE REVOLUTION: AI STRATEGIES FOR SUPERIOR GLOBAL HEALTH

CHAPTER 9- DIGITAL GREEN NEPHROLOGY: A PRE-DIALYSIS FRAMEWORK

Anwar Hamade

Department of Internal Medicine, AsterProcare Hospital- AlKhobar-KSA

Email: dr.anwar_hamade@hotmail.com

ABSTRACT

Managing Chronic Kidney Disease (CKD), mostly ESRD patients on hemodialysis, is a very resource-heavy process that leads to a large carbon footprint and hazardous waste. Most of the so-called 'Green Nephrology' efforts today remain largely focused on the optimization of dialysis machines for efficiency, remain largely reactive, focusing on optimizing dialysis machine efficiency rather than preventing the need for dialysis altogether. In this paper, we propose an interoperable health digital system that is proactive and integrate automated CDS and tele-nephrology into CKD management in pre-dialysis (Stages 1-4 CKD patients). A novel 'Carbon-Aware' CDS method that links nephrotoxic drug prescription with estimated environmental footprints is introduced. And with a theoretical Life Cycle Assessment (LCA), we show that a digital infrastructure that delays patients' need for dialysis by an average of 36 months can be responsible for an environmental offset of tonnes of CO_2 and million liters of water per 100 patients. In this way, our system can be a guide for health systems to make decisions for a greener roadmap without having to resort to complicated computational modeling.

Keywords: Green Nephrology; Digital Health Portals; Clinical Decision Support; Pre-Dialysis Management; Environmental Sustainability; Telemedicine Framework.

1. Introduction

Nowadays, transforming the intersection between chronic disease management and environmental sustainability on a global scale has become a major concern for modern healthcare systems. CKD, among other chronic diseases, has generated a significant share of the ecological footprint of the whole medical system [1]. In fact, the progression of this disease to End-Stage Renal Disease (ESRD) triggers the dependency of the patient's survival on renal replacement therapies, and among those therapies in-center hemodialysis (HD) is the most widely used. Still, viewing this from an industrial engineering point of view, a single conventional HD session imposes a substantial environmental burden: it consumes around 300 to 500 liters of water that needs to be purified to a very high degree (this purification is done by reverse osmosis systems), but the operation of the automated fluid pumps calls

for a constant supply of electrical power, and finally, each treatment session produces up to 2.5 kg of non-recyclable infectious plastic waste [2]. Given that this treatment is conducted thrice a week for the patient, the environmental degradation caused by it is profound.

Furthermore, patient logistics add another layer of carbon emissions. Patients with advanced CKD must go regularly to centralized urban medical centers, and this creates a transport-emission problem which affects urban air quality and adds to the traffic congestion in cities. As this allows the ongoing wasting of resources to persist, the concept of Green Nephrology has been introduced as a means of addressing these issues. It refers to the encouraging of clinical practices that result in less wastage, water saving and greater energy efficiency in rental units [3]. In fact, the implementation of green nephrology also faces an arduous difficulty; they are first and foremost reactive. They are looking to change the dialysis process itself rather than the patient reaching end-stage renal failure and needing dialysis. This concentration on the last stage is due to in reality primary care tracking through systems is often unsuccessful at both identifying and effectively managing early-stage CKD (Stages 1 to 4) so one of the consequences is a high rate of "crash" presentation into emergency dialysis.

Digital health informatics offers an effective solution to overcome these systemic bottlenecks through non-invasive, virtual interventions. This can be done by incorporating green nephrology practices in digital health portals, through a unified electronic health record system in the hospitals and through patient-oriented mobile applications. So, the healthcare networks which are currently working in a reactive, crisis-management mode will be able to change to an automated, preventive mode of operation.

This paper proposes an in-depth, qualitative system that illustrates the mechanism through which downstream digital infrastructure could bring a reduction in the rate of decline of kidney functions, improved drug therapy, and better home management of patient diets. More importantly, this system works as a roadmap for organizational and system-architecture change, showing that large sustainability gains can be thought of and implemented even without resorting to complex computation simulations or mathematical modeling.

2. Related Work

The interaction of digital health and environmental sustainability in nephrology is an emerging area. To properly place the suggested structure, existing literature should be reviewed in three separate areas: Green Nephrology initiatives, digital CKD management, and the conceptual gap connecting preventive informatics with carbon reduction.

2.1 Current Landscape of Green Nephrology

The concept of 'Green Nephrology' was initially introduced to quantify and minimize the alarming ecological footprint of renal replacement therapies. Recent life cycle assessments (LCAs) have reasonably highlighted the environmental burden of in-center HD, on water consumption (occasionally exceeding 300500 liters per session in some centers), as well as water treatment and energy-intensive machine operation [2]. So far, measures to promote green nephrology have been only 'downstream' and

mainly reactive. Efforts have focused on increasing dialysis efficiency (for example by installing water recycling machines and more energy-efficient reverse osmosis units and by reducing the use of disposables in dialysis units [6]), but at their core are implicitly based on accepting Really the treatment will take place and neglect the greener option of avoiding treatment altogether.

2.2 Digital Health and Tele-Nephrology Interventions

At the same time, these elements have also led to the development of a number of telemedicine systems, mobile health (mHealth) apps, and electronic health record (EHR) integrated Clinical Decision Support (CDS) programs for CKD management. There is evidence that remote patient monitoring (RPM) and educational applications have been successful at increasing blood pressure control, maintaining diet compliance, and lessening the slope of eGFR decline in pre-dialysis patients [4] . Besides, automated EHR alerts have been found to be highly effective in decreasing the order of nephrotoxic drugs in acute care settings [5]. Yet, such digital treatments are typically assessed solely based on their clinical benefits (e.g. mortality, hospital admission rates) or cost-effectiveness. The ability of these interventions to be environmental mitigation tools by averting the need for resource-intensive medical events has not been demonstrated.

2.3 The Intersecting Gap: Preventive Carbon Informatics

A review of the literature reveals a prominent silo effect: sustainability programs do not seem to connect with digital health informatics at all. Green IT in healthcare has mainly been about minimizing the energy consumption of data centers and other computational infrastructures. The potential of software to reduce the clinical carbon footprint has hardly been explored (e.g. a research work on healthcare IT carbon footprint). It is glaringly obvious that there are hardly any structures that revolve around clinical informatics (like automated CDS and asynchronous telehealth) to deliberately avoid high-carbon medical procedures.

This paper responds to this problem by presenting the notion of "Preventive Carbon Informatics." Instead of taking the software energy use as the starting point, the suggested model regards the digital infrastructure as a means of intervention. Integrating pre-dialysis digital health pathways with green nephrology goals, this research changes the sustainability discourse from merely improving dialysis to preventing the disease through informatics.

3. Methodology and System Architecture

The proposed system comprises a multi-level digital architecture linking the patient's home environment, primary care networks, and tertiary specialized nephrology units in one unified, closed-loop communications pipeline. The design is based on three main pillars, employing open-source data interoperability standards to prevent technical fragmentation (Figure 1).



Figure 1 Modernized nephrology integrated care system (NICS) architecture

3.1. Pillar 1: Automated Primary Care EHR Interface & CDS Layer

The basis of the system is the primary care EHR. Through an automated background analytics engine, the system monitors the routine lab results of the entire patient population.

- eGFR (estimated Glomerular Filtration Rate) Slope Analysis and Automated Triggering: The system, instead of waiting for the diagnosis to be made manually, computes the changes in serum creatinine and eGFR at different times. When a patient shows a consistent decrease in kidney function, the system generates an automatic alert and assigns the patient to a specialized pre-dialysis digital register.

  - Automated Nephrotoxic Prescribing Alerts: One of the major contributors to kidney failure is polypharmacy, mainly when nephrotoxic drugs are prescribed accidentally. The automated CDS layer keeps comparing the medication list with the renal-dosing guidelines that are regularly updated. If a primary care doctor tries to prescribe or renew a high-risk drug, such as non-steroidal anti-inflammatory drugs (NSAIDs), certain proton pump inhibitors, or specific antibiotics, the EHR will produce a hard-stop alert. This alert will not only require a clinical justification but will also give suggestions for safer, kidney-friendly options.

Standard eGFR slope analysis aside, the system introduces a Carbon-Aware Prescribing Alert. In case a doctor tries to prescribe a high-risk nephrotoxic drug (e.g. NSAIDs), the CDS doesn't just warn about the renal risk. Instead, it estimates the risk of ESRD progression due to the drug and converts that into an environmental impact estimate. The alert says: 'Warning: NSAID prescription may cause acute kidney injury. Unplanned dialysis results in roughly 3.5 tonnes of CO_2 emission per year. Consider alternative analgesics'

3.2. Pillar 2: The Multi-Disciplinary Tele-Nephrology Hub

Once a patient is registered in the pre-dialysis digital system, their care is managed through a comprehensive virtual dashboard. Usually, the care of a CKD patient involves visiting nephrologist, a renal dietitian, and a clinical pharmacist separately. With this traditional method, care not only gets divided but also the patient's travel increases a lot.

The Tele-Nephrology Hub integrates all these paths into one digital space:

- - The Shared Clinical Dashboard: Each clinician on this comprehensive ongoing care team will be monitoring a different component of the patient's disease progression. The nephrologist will be monitoring the structural progression of the disease; the clinical pharmacist will be identifying potential opportunities for modification of the medication regimen (e.g. with SGLT2 inhibitors and RAS blockers) while not harming the kidneys; and lastly the renal dietitian will be engaging with the patient on their diet.
- Asynchronous Consultation Workflows: Instead of video calls, which not only need high bandwidth but also impose strict scheduling, the hub focuses on asynchronous review of data. Doctors look at patient logs, make necessary changes to the treatment regimen, and update the patient's portal profile asynchronously, thereby increasing clinical efficiency.

3.3. Pillar 3: Patient-Facing Smart Portals

A patient-facing mobile application is the last point of contact that can be a digital health coach. The app is based on patient empowerment and changing behavior, which are essential in the progression of early-stage renal failure.

- Intelligent Nutritional and Fluid Management Module: This involves controlling the intake of sodium, potassium, and phosphorus, and protein to minimize the burden of kidneys. The app offers a simple, culturally relevant dietary recording tool. When a patient records a meal, the app assesses its effect on renal chemistry and offers help at once (e.g. it may recommend a low-sodium option, or it may alert you to a high-potassium item).
- Biometric and Adherence Sync: A portal ties in with digital blood pressure instruments and scales for consumers. A sudden increase in body weight can mean that the patient has retained an unsafe level of fluid. If a patient's weight or blood pressure is outside the limits of safety, the software ignores the usual time periods and issues an instant warning to the Tele-Nephrology Hub.

To mitigate the digital divide among the predominantly elderly CKD population, the portal incorporates 'Geriatric UI/UX" principles: large typography, high-contrast modes, and icon-based dietary logging that does not require typing. Biometric sync leverages Bluetooth Low Energy (BLE) and SMART on FHIR applications to automatically ingest data from consumer blood pressure cuffs and smart scales, removing manual data entry errors

4. Anticipated Impact and Discussion

As this study mainly designs a system architecture, not an actual clinical intervention, its effect is assessed by a theoretical logic model and a downstream environmental LCA. Here we delineate how the NICS cellular model functionally leads to the environmental and clinical targets, estimate the theoretical ecological offset, and identify the socio-technical barriers to the actual implementation of the system.

4.1 Theoretical Life Cycle Assessment (LCA) of Delayed Dialysis

In order to figure out the environmental benefits that will come after the implementation of the proposed plan, we performed a theoretical LCA based on the consumption of resources in in-center hemodialysis (HD) as depicted in the literature. The standard HD is estimated to need about 3.5 kWh of electrical energy per session while it also uses about 400 liters of water (including reverse osmosis reject water) per session [6, 7]. If a patient has dialysis three times a week, i.e. 156 sessions a year, then the baseline annual footprint of a single patient is 546 kWh of energy and 62,400 liters of water.

Through proactive preservation of eGFR, if the NICS system can bring postponement of dialysis initiation by 36 months, on average, for a hypothetical group of 100 patients, the theoretical environmental avoidance would be huge. Taking the standard grid emission factor of 0.42 kg CO_2 per kWh [8], the accumulated savings are summarized in Table 1.

Table 1 Theoretical Environmental Avoidance via 36-Month Dialysis Delay (Cohort of 100 Patients)

RESOURCE METRIC	PER PATIENT (ANNUAL BASELINE)	THEORETICAL AVOIDANCE CALCULATION (100 PATIENTS, 3 YEARS)	TOTAL PROJECTED SAVINGS
Energy Consumption	546 kWh	546 kWh × 3 years × 100 patients	163,800 kWh
Water Consumption	62,400 Liters	62,400 L × 3 years × 100 patients	18,720,000 Liters
Carbon Emissions (CO_2e)	229.3 kg CO_2	229.3 kg × 3 years × 100 patients	68,790 kg CO_2e

This life cycle assessment (LCA) reveals a major change in thinking: Preventive health formatics an function as an effective carbon offsetting mechanism. They can contribute towards carbon offsetting in a healthy way. For example, instead of concentrating digital resources flexibly on early-stage monitoring of health conditions, healthcare systems remain tethered to the highly industrialized and energy-intensive processes of end-stage renal replacement therapies. The environmental impacts of these processes are much reduced when this change is made.

4.2 Qualitative Sustainability and Accessibility Mechanisms

The ecological advantages indicated in the LCA are mainly the outcome of specific clinical processes in the NICS design. Table 2 lists these device elements and aligns them with the health outcomes, ecological benefits, and healthcare accessibility features that they are intended to achieve.

Table 2 NICS Component Impact Matrix

SYSTEM COMPONENT	TARGETED CLINICAL MECHANISM	ENVIRONMENTAL SAVINGS	ACCESSIBILITY DIVIDEND
Automated CDS Layer	Prevents drug-induced acute kidney injury (AKI); maintains stable eGFR slope.	Waste Prevention: Delays entry into dialysis, avoiding the generation of hundreds of kilograms of plastic bio-waste per patient.	Protects patients in remote or underserved areas from advanced disease complications due to delayed specialist availability.
Multi-Disciplinary Hub	Integrates pharmacy, nutrition, and nephrology into a single asynchronous care cycle.	Emission Reduction: Eliminates multiple, separate round-trip patient journeys to distinct clinical facilities.	Removes the physical and financial burden of travel, a primary barrier that frequently causes patients to miss appointments.
Patient-Facing Portal	Enhances home dietary compliance; provides real-time alerts for fluid overload.	Resource Conservation: Reduces emergency hospital admissions, lowering the consumption of single-use clinical supplies.	Offers real-time clinical guidance directly in the home, reducing the isolation often felt during chronic disease management.

4.3 Socio-Technical Barriers to Implementation

Although the NICS setup could theoretically have a major impact, its launch in the real world depends on the resolution of several socio-technical challenges first:

- Data Interoperability and Standardization: To ensure that the automated CDS layer functions smoothly not only within a single healthcare setting but also across primary, secondary, and tertiary care providers, the digital infrastructure must be able to support a common data communication protocol. The system's effectiveness depends on the use of Fast Healthcare Interoperability Resources (FHIR) and HL7 messaging standards. By implementing these standards, the distant rural clinic's lab work can be used to activate the decision-support rules in the urban hospital's electronic health record system instantly without data being lost at any point.
- The Digital Divide and User Experience: CKD mainly impacts older people who are also those most likely to suffer from lower digital literacy and vision problems due to old age. If the portal available to patients does not have excellent accessibility features, compliance with treatment will almost certainly fall, thereby compromising both clinical and environmental results. For one thing, to help solve the digital divide, the health systems that are rolling out NICS should make the digital portal available to everyone by setting up "device lending libraries" for patients who do not have the means to buy devices while at the same time putting in place SMS/USSD fallback systems for the people who do not own smartphones or have broadband access. And the interface must be very user-friendly and must follow the design principles for the elderly like large font sizes, high-contrast colors, and meal logging through icons.

- Clinical Burden and Alert Fatigue: Physicians are almost constantly receiving software notification, which may cause them to get used to the alerts and next ignore even those, which are important. One solution to this would be that the NICS, CDS strictly sticks to the "Five Rights of CDS" (the right information, the right person, the right format, the right channel, and the right time). It should be further argued that the system must implement Tiered Alert Logic so that only very serious alerts like a possible deadly drug interaction or a critically low eGFR are considered for a "hard-stop" or workflow interruption while lower-level suggestions are delivered silently into the patient chart.

4.4 Limitations

This proposed setup needs to be judged considering several restrictions. First, the NICS model is theoretical and uses an environmental offset figure derived from a theoretical scenario rather than data obtained from a real clinical pilot. The estimated environmental benefits rest on the assumption that the digital interventions will be able to delay the progress of dialysis by an average of 36 months; Yet, in the real world, patient adherence to digital portals may be lower than the ideal which might cause a reduction in both clinical and environmental benefits. Besides, although the structure seeks to lower the clinical carbon footprint, it is still subject to the "Green IT" paradox: the extra data center energy consumption needed to host cloud-based asynchronous telehealth hubs, to process continuous biometric data, and to conduct background EHR analytics was not measured in this preliminary model. Last, the scope of the structure may also be limited in under-resourced healthcare areas where the primary care EHR infrastructure and patient internet connectivity are inadequate to meet the proposed standards for interoperability.

5. Conclusions and Future Work

In this paper, the authors outlined the NICS setup and showed that through the combination of digital health portals and Green Nephrology principles it is possible to have a sustainable pathway for pre-dialysis care. By making a change in the clinical focus from reactive dialysis optimization to proactive prevention supported by informatics - i.e. through automated EHR interventions, asynchronous multi-disciplinary care, and patient-facing tools for behavioral change - health systems can not only improve patient outcomes but at the same time reduce drastically their carbon and water footprints. The suggested "Carbon-Aware" CDS and the quantified environmental offsets demonstrate that health informatics for prevention is a key, although quite overlooked, instrument for healthcare sustainability.

The introduction of digital patients' early-stage monitoring through such a model is a pivotal element and core driver of three large-scale impacts: improving patient outcomes, bringing to all an equal opportunity of accessing expert healthcare, and minimizing the environmental impact of healthcare delivery. By avoiding or postponing the initiation of dialysis, which is a very resource-demanding treatment, this approach demonstrates that health informatics for prevention is also a key tool for environmental sustainability. That means, the present setup offers healthcare organizations, digital designers, and policy makers with a clear and hands-on reference point to plan and implement

sustainable tele-nephrology networks without the need for sophisticated computational modeling or simulation software.

Future work will be directed towards the implementation of this conceptual architecture in a measurable pilot study. Phase 1 after this will be the development of a localized, simulated LCA model that uses regional grid emission data to estimate more precisely the theoretical carbon savings. Next, we intend to conduct a small clinical pilot of the Carbon-Aware CDS module in a primary care network to experimentally assess its effect on nephrotoxic prescribing rates, clinician acceptability, and alert fatigue metrics.

References

1. Barraclough, K.A., A. Cases, M.J. Eckelman, C. Germond-Duret, C. Zoccali, N. Embleton, A. Wright, L. Hubbert, L. Nicholson, S. Barone, C. Cabrera, J.J.G. Sanchez, V. Selvarajah, and R. Pecoits-Filho, *International Environmental Impact of CKD Care.* Kidney Int Rep, 2026. **11**(2): p. 103662.
2. Arias-Guillén, M., R. Martínez Cadenas, M. Gómez, N. Martín Vaquero, G. Pereda, J. Audije-Gil, J. Portillo, M. Quintela, I. Castaño, A. Luque, F. Maduell, A. Ortiz, B. Duane, and M.D. Arenas, *Environmental challenges in hemodialysis: Exploring the road to sustainability.* Nefrología (English Edition), 2024. **44**(6): p. 784-795.
3. Barraclough, K.A., N. Berman-Parks, V. Jha, G.B. Piccoli, C. Stigant, B. Talbot, F. Tarrass, M. Cheung, J.M. King, M.E. Grams, M. Jadoul, J.E. Flythe, F. Adshead, C.M. Avesani, S. Bavanandan, J. Beige, M. Ben Hmida, P.J. Blankestijn, C. Bonnet, E.A. Brown, C.T. Chan, E. Chang, C. Chazot, R. Claure-Del Granado, R. Danner, A. Davenport, G. Donati, H. Fessi, M.W.Y. Foo, W.W.S. Fung, K.G.F. Gerritsen, R.A. Gomez Acevedo, S.O. Haddad, M. Harber, A.M. Huml, M.A. Josephson, R. Kazancioğlu, S. Kishi, S. Knöller, G.J. Ko, M.K. Kuhlmann, H.R. Mian, B. Mihaylova, A. Monecke, F. Mortimer, G.P. Munoz-Figueroa, R.A. Mustafa, A. Niang, J. Perl, R. Picillo, F. Poia, M. Salani, A. Seman, J. Speller, P. Stenvinkel, P.E. Stevens, R.S. Suri, M. Torreggiani, I.I. Ulasi, R. Vanholder, C.K. Velumurugan, S. Watnick, J. Waugh, F.P. Wieringa, and J. Yang, *Green dialysis: environmentally sustainable care, growth, and innovation: conclusions from a Kidney Disease: Improving Global Outcomes (KDIGO) Controversies Conference.* Kidney International, 2026. **110**(1): p. 42-60.
4. Mata-Lima, A., A.R. Paquete, and J.J. Serrano-Olmedo, *Remote patient monitoring and management in nephrology: A systematic review.* Nefrología, 2024. **44**(5): p. 639-667.
5. Kashani, K.B., *Automated acute kidney injury alerts.* Kidney International, 2018. **94**(3): p. 484-490.
6. Barraclough, K.A., S. Moller, S. Blair, R. Knight, J.W. Agar, S. McAlister, A. White, and M. Sypek, *Updating the Data: The Resource Consumption of Modern-Day Hemodialysis Systems.* Kidney Int Rep, 2024. **9**(5): p. 1521-1524.
7. Rydzewska-Rosołowska, A., I. Głowińska, K. Kakareko, A. Pietruczuk, and T. Hryszko, *How low can we go with the dialysate flow? A retrospective study on the safety and adequacy of a water-saving dialysis prescription.* Clin Kidney J, 2024. **17**(8): p. sfae238.
8. Beige, J., S. Knöller, M. Pachmann, F. Sommer, H.P. Barth, M. Masanneck, W. Kleophas, R. Schaffron, S. Stracke, K. deGroot, J. Weinmann-Menke, S.C. Boedecker-Lips, and R. Vanholder, *A website calculator to benchmark the carbon footprint of haemodialysis.* Nephrology Dialysis Transplantation, 2026.